



# Ordering Guide

## Specialist Application Handles for BS Fuse Switches

For handle style and function see page 4

	Rod/ball handle		Flange Mounted	internal mounted	Double arm kit
	TYPE A	TYPE B	TYPE H	TYPE I	
UFS32A1	IP65 61978-2 Padlock Kit included	-		62146-1	-
US32					
UFS63					
UFS100A3	IP65 61572-2 Padlock Kit included	IP65 61572-4 Padlock Kit included	IP65 61979-3	61915-1	To convert standard moulded handles to double arm 61853-1
UFS160					
UFS160AC22					
UFS200					
UFS315					
UFS400				62108-1	
UFS630	IP65 Standard 62337-1 Asymmetric 62431-1 Padlock Kit included	IP65 Standard 62337-2 Asymmetric 62431-2 Padlock Kit included	62536-1	62528-1	-
UFS800C3					
UFS800	IP65 62337-1 Padlock Kit included	IP65 62337-2 Padlock Kit included	-	-	-

### EXTRA LONG SHAFTS FOR STANDARD MOULDED HANDLES

SWITCH	LENGTH	Outrigger c/w 320mm shaft		225mm Special	320mm Special Note 1:	500mm Special Note 1:	600mm Special Note 1:
	distance between base & inside of door	Part No.					
UFS32A1 UFS32 UFS63 6mm sq shaft	-	-		HHL46188	-	-	-
UFS100A3 UFS160 UFS160AC22 8mm sq shaft	416mm	60793-3		-	HHL44093	HHL46051	HHL46052
UFS200 UFS315 8mm sq shaft	430mm	60793-3		-	HHL44093 Note 2:	HHL46051 Note 2:	HHL46052 Note 2:
UFS400 UFS630 10mm sq shaft	510mm	62090-3		-	HHL46272	-	-
UFS800C3 UFS800	-	-		-	-	-	-

### EXTRA LONG SHAFT FOR ROD/BALL HANDLE

UFS100A3 UFS160 UFS160AC22 UFS200 UFS315 8mm sq shaft	-	-		-	61930-2	-	-
--	---	---	--	---	---------	---	---

**Note 1:** Shafts 320mm and above should be supported

**Note 2:** 6 pole switches have 10mm sq shafts - max length permissible 320mm